



LOUDSPEAKER CABLE - RED & BLACK

TECNICAL FEATURES

CONDUCTORS

Flexible red copper

INSULATION

PVC Red & Black

ELECTRICAL FEATURES

TEST VOLTAGE

1000 V

INSULATION RESISTANCE

> 200 MΩ/Km

TEMPERATURE RANGE

-10°/ +70°

BENDING RADIUS

10 X Ø

STANDARDS

Insulation and sheath

CEI EN 50363

Flame retardant

IEC 60332-1-2

coexistence with cables CAT. 1

UNEL 36762

European directive Rohs 2011/65/EU

PACKAGING AVAILABLE



100/200 mt.



500 mt.

MARKING

Without marking



PRODUCTS:

Code	Nominal Section	Packaging	Copper	Cond. Resistance Ohm/Km	Jacket colour
R/N2B	LOUDSPEAKER CABLE RED & BLACK 2X0.50	M100 - M200 - B500*	8X0.25	45	B/R
R/N2K	LOUDSPEAKER CABLE RED & BLACK 2X0.75	M100 - M200 - B500*	12X0.25	32	B/R
R/N2C	LOUDSPEAKER CABLE RED & BLACK 2X1.00	M100 - M200 - B500*	16X0.25	23	B/R
R/N2R	LOUDSPEAKER CABLE RED & BLACK 2X1.50	M100 - M200 - B500*	24X0.25	16	B/R

*Other packaging available at request